

NAME

gsasl_free - API function

SYNOPSIS

```
#include <gsasl.h>
```

```
void gsasl_free(void * ptr);
```

ARGUMENTS

void * ptr memory pointer

DESCRIPTION

Invoke free(*ptr*) to de-allocate memory pointer. Typically used on strings allocated by other libgsasl functions.

This is useful on Windows where libgsasl is linked to one CRT and the application is linked to another CRT. Then malloc/free will not use the same heap. This happens if you build libgsasl using mingw32 and the application with Visual Studio.

SINCE

0.2.19

REPORTING BUGS

Report bugs to <bug-gsasl@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU SASL home page: <http://www.gnu.org/software/gsasl/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

```
info gsasl
```

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/gsasl/manual/>