

NAME

gsasl_property_get - API function

SYNOPSIS

```
#include <gsasl.h>
```

```
const char * gsasl_property_get(Gsasl_session * sctx, Gsasl_property prop);
```

ARGUMENTS

Gsasl_session * sctx
session handle.

Gsasl_property prop
enumerated value of Gsasl_property type, indicating the type of data in *data* .

DESCRIPTION

Retrieve the data stored in the session handle for given property *prop* , possibly invoking the application callback to get the value.

The pointer is to live data, and must not be deallocated or modified in any way.

This function will invoke the application callback, using **gsasl_callback()**, when a property value is not known.

Return value: Return data for property, or NULL if no value known.

SINCE

0.2.0

REPORTING BUGS

Report bugs to <bug-gsasl@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU SASL home page: <http://www.gnu.org/software/gsasl/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

info gsasl

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/gsasl/manual/>