

NAME

gsasl_property_set - API function

SYNOPSIS

```
#include <gsasl.h>
```

```
int gsasl_property_set(Gsasl_session * sctx, Gsasl_property prop, const char * data);
```

ARGUMENTS

Gsasl_session * sctx

session handle.

Gsasl_property prop

enumerated value of Gsasl_property type, indicating the type of data in *data* .

const char * data

zero terminated character string to store.

DESCRIPTION

Make a copy of *data* and store it in the session handle for the indicated property *prop* .

You can immediately deallocate *data* after calling this function, without affecting the data stored in the session handle.

Return value: **GSASL_OK** iff successful, otherwise **GSASL_MALLOC_ERROR**.

SINCE

0.2.0

REPORTING BUGS

Report bugs to <bug-gsasl@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU SASL home page: <http://www.gnu.org/software/gsas/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

info gsasl

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/gsasl/manual/>