

**NAME**

**i2s ASN1\_IA5STRING**, **s2i ASN1\_IA5STRING**, **i2s ASN1\_INTEGER**, **s2i ASN1\_INTEGER**,  
**i2s ASN1\_OCTET\_STRING**, **s2i ASN1\_OCTET\_STRING**, **i2s ASN1 ENUMERATED**,  
**i2s ASN1 ENUMERATED\_TABLE**, **i2s ASN1\_UTF8STRING**, **s2i ASN1\_UTF8STRING** - convert  
objects from/to ASN.1/string representation

**SYNOPSIS**

```
#include <openssl/x509v3.h>

char *i2s ASN1_IA5STRING(X509V3_EXT_METHOD *method, ASN1_IA5STRING *ia5);
ASN1_IA5STRING *s2i ASN1_IA5STRING(X509V3_EXT_METHOD *method,
X509V3_CTX *ctx, const char *str);

char *i2s ASN1_INTEGER(X509V3_EXT_METHOD *method, const ASN1_INTEGER *a);
ASN1_INTEGER *s2i ASN1_INTEGER(X509V3_EXT_METHOD *method, const char *value);

char *i2s ASN1_OCTET_STRING(X509V3_EXT_METHOD *method,
const ASN1_OCTET_STRING *oct);
ASN1_OCTET_STRING *s2i ASN1_OCTET_STRING(X509V3_EXT_METHOD *method,
X509V3_CTX *ctx, const char *str);

char *i2s ASN1_ENUMERATED(X509V3_EXT_METHOD *method, const ASN1_ENUMERATED *a);
char *i2s ASN1_ENUMERATED_TABLE(X509V3_EXT_METHOD *method,
const ASN1_ENUMERATED *e);

char *i2s ASN1_UTF8STRING(X509V3_EXT_METHOD *method,
ASN1_UTF8STRING *utf8);
ASN1_UTF8STRING *s2i ASN1_UTF8STRING(X509V3_EXT_METHOD *method,
X509V3_CTX *ctx, const char *str);
```

**DESCRIPTION**

These functions convert OpenSSL objects to and from their ASN.1/string representation. This function is used for **X509v3** extensions.

**NOTES**

The letters **i** and **s** in **i2s** and **s2i** stand for "internal" (that is, an internal C structure) and string respectively. So **i2s ASN1\_IA5STRING()** converts from internal to string.

It is the caller's responsibility to free the returned string. In the **i2s ASN1\_IA5STRING()** function the string is copied and the ownership of the original string remains with the caller.

**RETURN VALUES**

**i2s ASN1\_IA5STRING()** returns the pointer to a IA5 string or NULL if an error occurs.

**s2i ASN1 IA5STRING()** return a valid **ASN1\_IA5STRING** structure or NULL if an error occurs.

**i2s ASN1\_INTEGER()** return a valid string or NULL if an error occurs.

**s2i ASN1\_INTEGER()** returns the pointer to a **ASN1\_INTEGER** structure or NULL if an error occurs.

**i2s ASN1 OCTET STRING()** returns the pointer to a **OCTET\_STRING** string or NULL if an error occurs.

**s2i ASN1 OCTET STRING()** return a valid **ASN1\_OCTET\_STRING** structure or NULL if an error occurs.

**i2s ASN1 ENUMERATED()** return a valid string or NULL if an error occurs.

**s2i ASN1 ENUMERATED()** returns the pointer to a **ASN1\_ENUMERATED** structure or NULL if an error occurs.

**s2i ASN1 UTF8STRING()** return a valid **ASN1\_UTF8STRING** structure or NULL if an error occurs.

**i2s ASN1 UTF8STRING()** returns the pointer to a UTF-8 string or NULL if an error occurs.

## HISTORY

**i2s ASN1 UTF8STRING()** and **s2i ASN1 UTF8STRING()** were made public in OpenSSL 3.0.

## COPYRIGHT

Copyright 2020-2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the "License"). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.