

NAME

`ibv_modify_qp` - modify the attributes of a queue pair (QP)

SYNOPSIS

```
#include <infiniband/verbs.h>
```

```
int ibv_modify_qp(struct ibv_qp *qp, struct ibv_qp_attr *attr,
                 int attr_mask);
```

DESCRIPTION

`ibv_modify_qp()` modifies the attributes of QP *qp* with the attributes in *attr* according to the mask *attr_mask*. The argument *attr* is an `ibv_qp_attr` struct, as defined in `<infiniband/verbs.h>`.

```
struct ibv_qp_attr {
    enum ibv_qp_state    qp_state;          /* Move the QP to this state */
    enum ibv_qp_state    cur_qp_state;      /* Assume this is the current QP state */
    enum ibv_mtu         path_mtu;         /* Path MTU (valid only for RC/UC QPs) */
    enum ibv_mig_state   path_mig_state;    /* Path migration state (valid if HCA supports APM) */
    uint32_t             qkey;             /* Q_Key for the QP (valid only for UD QPs) */
    uint32_t             rq_psn;          /* PSN for receive queue (valid only for RC/UC QPs) */
    uint32_t             sq_psn;          /* PSN for send queue (valid only for RC/UC QPs) */
    uint32_t             dest_qp_num;      /* Destination QP number (valid only for RC/UC QPs) */
    int                  qp_access_flags;  /* Mask of enabled remote access operations (valid only for RC/UC QPs) */
    struct ibv_qp_cap    cap;              /* QP capabilities (valid if HCA supports QP resizing) */
    struct ibv_ah_attr   ah_attr;          /* Primary path address vector (valid only for RC/UC QPs) */
    struct ibv_ah_attr   alt_ah_attr;      /* Alternate path address vector (valid only for RC/UC QPs) */
    uint16_t             pkey_index;       /* Primary P_Key index */
    uint16_t             alt_pkey_index;    /* Alternate P_Key index */
    uint8_t              en_sqd_async_notify; /* Enable SQD.drained async notification (Valid only if qp_state is IBV_QPS_DRAINED) */
    uint8_t              sq_draining;      /* Is the QP draining? Irrelevant for ibv_modify_qp() */
    uint8_t              max_rd_atomic;    /* Number of outstanding RDMA reads & atomic operations on the qp */
    uint8_t              max_dest_rd_atomic; /* Number of responder resources for handling incoming RDMA reads */
    uint8_t              min_rnr_timer;    /* Minimum RNR NAK timer (valid only for RC QPs) */
    uint8_t              port_num;         /* Primary port number */
    uint8_t              timeout;          /* Local ack timeout for primary path (valid only for RC QPs) */
    uint8_t              retry_cnt;        /* Retry count (valid only for RC QPs) */
    uint8_t              rnr_retry;        /* RNR retry (valid only for RC QPs) */
    uint8_t              alt_port_num;     /* Alternate port number */
    uint8_t              alt_timeout;      /* Local ack timeout for alternate path (valid only for RC QPs) */
    uint32_t             rate_limit;       /* Rate limit in kbps for packet pacing */
};
```

```
};
```

For details on struct `ibv_qp_cap` see the description of `ibv_create_qp()`. For details on struct `ibv_ah_attr` see the description of `ibv_create_ah()`.

The argument `attr_mask` specifies the QP attributes to be modified. The argument is either 0 or the bitwise OR of one or more of the following flags:

IBV_QP_STATE Modify `qp_state`

IBV_QP_CUR_STATE Set `cur_qp_state`

IBV_QP_EN_SQD_ASYNC_NOTIFY Set `en_sqd_async_notify`

IBV_QP_ACCESS_FLAGS Set `qp_access_flags`

IBV_QP_PKEY_INDEX Set `pkey_index`

IBV_QP_PORT Set `port_num`

IBV_QP_QKEY Set `qkey`

IBV_QP_AV Set `ah_attr`

IBV_QP_PATH_MTU Set `path_mtu`

IBV_QP_TIMEOUT Set `timeout`

IBV_QP_RETRY_CNT Set `retry_cnt`

IBV_QP_RNR_RETRY Set `rnr_retry`

IBV_QP_RQ_PSN Set `rq_psn`

IBV_QP_MAX_QP_RD_ATOMIC Set `max_rd_atomic`

IBV_QP_ALT_PATH Set the alternative path via: `alt_ah_attr`, `alt_pkey_index`, `alt_port_num`, `alt_timeout`

IBV_QP_MIN_RNR_TIMER Set `min_rnr_timer`

IBV_QP_SQ_PSN Set sq_psn

IBV_QP_MAX_DEST_RD_ATOMIC Set max_dest_rd_atomic

IBV_QP_PATH_MIG_STATE Set path_mig_state

IBV_QP_CAP Set cap

IBV_QP_DEST_QPN Set dest_qp_num

IBV_QP_RATE_LIMIT Set rate_limit

RETURN VALUE

ibv_modify_qp() returns 0 on success, or the value of errno on failure (which indicates the failure reason).

NOTES

If any of the modify attributes or the modify mask are invalid, none of the attributes will be modified (including the QP state).

Not all devices support resizing QPs. To check if a device supports it, check if the **IBV_DEVICE_RESIZE_MAX_WR** bit is set in the device capabilities flags.

Not all devices support alternate paths. To check if a device supports it, check if the **IBV_DEVICE_AUTO_PATH_MIG** bit is set in the device capabilities flags.

The following tables indicate for each QP Transport Service Type, the minimum list of attributes that must be changed upon transitioning QP state from: Reset --> Init --> RTR --> RTS.

For QP Transport Service Type **IBV_QPT_UD**:

Next state Required attributes

----- -----
Init **IBV_QP_STATE, IBV_QP_PKEY_INDEX, IBV_QP_PORT,
 IBV_QP_QKEY**

RTR **IBV_QP_STATE**

RTS **IBV_QP_STATE, IBV_QP_SQ_PSN**

For QP Transport Service Type **IBV_QPT_UC**:

Next state Required attributes

```

-----
Init      IBV_QP_STATE, IBV_QP_PKEY_INDEX, IBV_QP_PORT,
          IBV_QP_ACCESS_FLAGS
RTR      IBV_QP_STATE, IBV_QP_AV, IBV_QP_PATH_MTU,
          IBV_QP_DEST_QPN, IBV_QP_RQ_PSN
RTS      IBV_QP_STATE, IBV_QP_SQ_PSN

```

For QP Transport Service Type **IBV_QPT_RC**:

Next state Required attributes

```

-----
Init      IBV_QP_STATE, IBV_QP_PKEY_INDEX, IBV_QP_PORT,
          IBV_QP_ACCESS_FLAGS
RTR      IBV_QP_STATE, IBV_QP_AV, IBV_QP_PATH_MTU,
          IBV_QP_DEST_QPN, IBV_QP_RQ_PSN,
          IBV_QP_MAX_DEST_RD_ATOMIC, IBV_QP_MIN_RNR_TIMER
RTS      IBV_QP_STATE, IBV_QP_SQ_PSN, IBV_QP_MAX_QP_RD_ATOMIC,
          IBV_QP_RETRY_CNT, IBV_QP_RNR_RETRY, IBV_QP_TIMEOUT

```

For QP Transport Service Type **IBV_QPT_RAW_PACKET**:

Next state Required attributes

```

-----
Init      IBV_QP_STATE, IBV_QP_PORT
RTR      IBV_QP_STATE
RTS      IBV_QP_STATE

```

SEE ALSO

ibv_create_qp(3), ibv_destroy_qp(3), ibv_query_qp(3), ibv_create_ah(3)

AUTHORS

Dotan Barak <dotanba@gmail.com>