

**NAME**

idn2\_strerror\_name - API function

**SYNOPSIS**

```
#include <idn2.h>
```

```
const char * idn2_strerror_name(int rc);
```

**ARGUMENTS**

int rc            return code from another libidn2 function.

**DESCRIPTION**

Convert internal libidn2 error code to a string corresponding to internal header file symbols. For example, `idn2_strerror_name(IDN2_MALLOC)` will return the string "IDN2\_MALLOC".

The caller must not attempt to de-allocate the returned string.

Return value: A string corresponding to error code symbol.

**REPORTING BUGS**

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <https://www.gnu.org/gethelp/>

Libidn2 home page: <https://www.gnu.org/software/libidn2/>

**COPYRIGHT**

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **libidn2** is maintained as a Texinfo manual. If the **info** and **libidn2** programs are properly installed at your site, the command

```
info libidn2
```

should give you access to the complete manual. As an alternative you may obtain the manual from:

```
https://www.gnu.org/software/libidn/libidn2/manual/
```