

NAME

idn2_to_ascii_lz - API function

SYNOPSIS

```
#include <idn2.h>
```

```
int idn2_to_ascii_lz(const char * input, char ** output, int flags);
```

ARGUMENTS

const char * input

zero terminated input UTF-8 string.

char ** output

pointer to newly allocated output string.

int flags

optional **idn2_flags** to modify behaviour.

DESCRIPTION

Convert a domain name in locale's encoding to ASCII string using the IDNA2008 rules. The domain name may contain several labels, separated by dots. The output buffer must be deallocated by the caller.

The default behavior of this function (when flags are zero) is to apply the IDNA2008 rules without the TR46 amendments. As the TR46 non-transitional processing is nowadays ubiquitous, when unsure, it is recommended to call this function with the **IDN2_NONTRANSITIONAL** and the **IDN2_NFC_INPUT** flags for compatibility with other software.

RETURNS

IDN2_OK on success, or error code. Same as described in **idn2_lookup_ul()** documentation.

SINCE

2.0.0

REPORTING BUGS

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <https://www.gnu.org/gethelp/>

Libidn2 home page: <https://www.gnu.org/software/libidn2/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libidn2** is maintained as a Texinfo manual. If the **info** and **libidn2** programs are properly installed at your site, the command

info libidn2

should give you access to the complete manual. As an alternative you may obtain the manual from:

<https://www.gnu.org/software/libidn/libidn2/manual/>