

NAME

idna_to_ascii_8z - API function

SYNOPSIS

```
#include <idna.h>
```

```
int idna_to_ascii_8z(const char * input, char ** output, int flags);
```

ARGUMENTS

const char * input

zero terminated input UTF-8 string.

char ** output

pointer to newly allocated output string.

int flags

an **Idna_flags** value, e.g., **IDNA_ALLOW_UNASSIGNED** or **IDNA_USE_STD3_ASCII_RULES**.

DESCRIPTION

Convert UTF-8 domain name to ASCII string. The domain name may contain several labels, separated by dots. The output buffer must be deallocated by the caller.

Return value: Returns **IDNA_SUCCESS** on success, or error code.

REPORTING BUGS

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU Libidn home page: <http://www.gnu.org/software/libidn/>

COPYRIGHT

Copyright (C) 2002-2021 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libidn** is maintained as a Texinfo manual. If the **info** and **libidn** programs are properly installed at your site, the command

info libidn

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/libidn/manual/>