

**NAME**

**iprolog** - maintain the iprop log file

**SYNOPSIS**

**iprolog** [--version] [-h | --help] *command*

**iprolog truncate**[-c *file* | --config-file=*file*] [-r *string* | --realm=*string*] [-h | --help]

**iprolog dump**[-c *file* | --config-file=*file*] [-r *string* | --realm=*string*] [-h | --help]

**iprolog replay**[--start-version=*version-number*] [--end-version=*version-number*]  
[-c *file* | --config-file=*file*] [-r *string* | --realm=*string*] [-h | --help]

**DESCRIPTION**

Supported options:

**--version**

**-h, --help**

*command* can be one of the following:

**truncate**

**-c *file*, --config-file=*file***  
configuration file

**-r *string*, --realm=*string***  
realm

Truncates the log. Sets the new logs version number for the to the last entry of the old log. If the log is truncated by emptying the file, the log will start over at the first version (0).

**dump**

**-c *file*, --config-file=*file***  
configuration file

**-r *string*, --realm=*string***  
realm

Print out all entries in the log to standard output.

replay

**--start-version**=*version-number*

start replay with this version

**--end-version**=*version-number*

end replay with this version

**-c** *file*, **--config-file**=*file*

configuration file

**-r** *string*, **--realm**=*string*

realm

Replay the changes from specified entries (or all if none is specified) in the transaction log to the database.

last-version

**-c** *file*, **--config-file**=*file*

configuration file

**-r** *string*, **--realm**=*string*

realm

prints the version of the last log entry.

## SEE ALSO

iprop(8)