#### **NAME**

**kbdmap**, **vidfont** - front end for syscons and vt

#### **SYNOPSIS**

### DESCRIPTION

The **kbdmap** utility allows easy setting of available keymaps. The **vidfont** command allows the setting of fonts. Both examine a database for the keymaps and fonts. Descriptions are in English by default, but may also be in other languages. These programs are interactive and expect to run in a terminal to get required input (e.g., a keymap selection) from the user.

It is strongly recommended to not choose MSDOS codepage keymaps or fonts. Use the ISO standard version if available! X11 does not support MSDOS codepage.

The following options are available:

- **-K** Run as command **kbdmap**.
- **-V** Run as command **vidfont**.

# -d, -default

Use default language. Ignore LANG environment variable.

### -h, -help

Print options and exit.

## -l, -lang language

Use language for description and menu.

#### -p, -print

Print description of available keymaps or fonts to stdout and exit.

### -r, -restore

Load default font from /etc/rc.conf.

### -s, -show

Show currently supported languages and exit.

#### -v, -verbose

More warnings.

#### **ENVIRONMENT**

LANG preferred language

#### **FILES**

/usr/share/syscons/keymaps/INDEX.keymaps

/usr/share/vt/keymaps/INDEX.keymaps database for keymaps

/usr/share/syscons/fonts/INDEX.fonts

/usr/share/vt/fonts/INDEX.fonts database for fonts

/etc/rc.conf default font

/usr/local/share/locale/locale.alias describe common LANG values

### **SEE ALSO**

dialog(1), kbdcontrol(1), vidcontrol(1), syscons(4), vt(4), kbdmap(5), rc.conf(5)

#### **HISTORY**

The **kbdmap** and **vidfont** commands appeared in FreeBSD 2.1.

### **AUTHORS**

Wolfram Schneider <*wosch@FreeBSD.org>* wrote the original Perl version. The current version was rewritten in C by Jonathan Belson <*jon@witchspace.com>* for FreeBSD 5.0.

### **BUGS**

The **kbdmap** and **vidfont** utilities work only on a (virtual) console and not with X11.