

NAME

`ldns_get_rr_list_hosts_frm_file`, `ldns_get_rr_list_hosts_frm_fp`, `ldns_get_rr_list_hosts_frm_fp_l` -
parse /etc/hosts file

SYNOPSIS

```
#include <stdint.h>
#include <stdbool.h>

#include <ldns/ldns.h>

ldns_rr_list* ldns_get_rr_list_hosts_frm_file(char *filename);

ldns_rr_list* ldns_get_rr_list_hosts_frm_fp(FILE *fp);

ldns_rr_list* ldns_get_rr_list_hosts_frm_fp_l(FILE *fp, int *line_nr);
```

DESCRIPTION

`ldns_get_rr_list_hosts_frm_file()` wade through fp (a /etc/hosts like file) and return a rr_list containing all the defined hosts in there

filename: the filename to use (NULL for /etc/hosts)

Returns ldns_rr_list * with the names

`ldns_get_rr_list_hosts_frm_fp()` wade through fp (a /etc/hosts like file) and return a rr_list containing all the defined hosts in there

fp: the file pointer to use

Returns ldns_rr_list * with the names

`ldns_get_rr_list_hosts_frm_fp_l()` wade through fp (a /etc/hosts like file) and return a rr_list containing all the defined hosts in there

fp: the file pointer to use

line_nr: pointer to an integer containing the current line number (for debugging purposes)

Returns ldns_rr_list * with the names

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at

<http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_rr_list, *ldns_rr*. And **perldoc Net::DNS**, **RFC1034**, **RFC1035**, **RFC4033**, **RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.