

**NAME**

ldns\_key\_buf2dsa, ldns\_key\_buf2rsa - convert buffer to openssl key

**SYNOPSIS**

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
DSA* ldns_key_buf2dsa(const ldns_buffer *key);
```

```
RSA* ldns_key_buf2rsa(const ldns_buffer *key);
```

**DESCRIPTION**

*ldns\_key\_buf2dsa()* converts a buffer holding key material to a DSA key in openssl.

**key:** the key to convert

Returns a DSA \* structure with the key material

*ldns\_key\_buf2rsa()* converts a buffer holding key material to a RSA key in openssl.

**key:** the key to convert

Returns a RSA \* structure with the key material

**AUTHOR**

The ldns team at NLnet Labs.

**REPORTING BUGS**

Please report bugs to [ldns-team@nlnetlabs.nl](mailto:ldns-team@nlnetlabs.nl) or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

**COPYRIGHT**

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

**SEE ALSO**

*ldns\_key\_rr2ds*. And **perldoc Net::DNS**, **RFC1034**, **RFC1035**, **RFC4033**, **RFC4034** and **RFC4035**.

**REMARKS**

This manpage was automatically generated from the ldns source code.