

NAME

ldns_key_free, ldns_key_deep_free, ldns_key_list_free - free a ldns_key

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
void ldns_key_free(ldns_key *key);
```

```
void ldns_key_deep_free(ldns_key *key);
```

```
void ldns_key_list_free(ldns_key_list *key_list);
```

DESCRIPTION

ldns_key_free() frees a key structure, but not its internal data structures

key: the key object to free

ldns_key_deep_free() frees a key structure and all its internal data structures, except the data set by *ldns_key_set_external_key()*

key: the key object to free

ldns_key_list_free() Frees a key list structure

key_list: the key list object to free

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_key. And **perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.