

**NAME**

ldns\_key\_free, ldns\_key\_deep\_free, ldns\_key\_list\_free - free a ldns\_key

**SYNOPSIS**

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
void ldns_key_free(ldns_key *key);
```

```
void ldns_key_deep_free(ldns_key *key);
```

```
void ldns_key_list_free(ldns_key_list *key_list);
```

**DESCRIPTION**

*ldns\_key\_free()* frees a key structure, but not its internal data structures

**key:** the key object to free

*ldns\_key\_deep\_free()* frees a key structure and all its internal data structures, except the data set by *ldns\_key\_set\_external\_key()*

**key:** the key object to free

*ldns\_key\_list\_free()* Frees a key list structure

**key\_list:** the key list object to free

**AUTHOR**

The ldns team at NLnet Labs.

**REPORTING BUGS**

Please report bugs to [dns-team@nlnetlabs.nl](mailto:dns-team@nlnetlabs.nl) or on GitHub at <https://github.com/NLnetLabs/ldns/issues>

**COPYRIGHT**

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

**SEE ALSO**

*ldns\_key*. And **perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034** and **RFC4035**.

**REMARKS**

This manpage was automatically generated from the ldns source code.