

NAME

ldns_key_list_push_key, ldns_key_list_pop_key - manipulate ldns_key_list

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
bool ldns_key_list_push_key(ldns_key_list *key_list, ldns_key *key);
```

```
ldns_key* ldns_key_list_pop_key(ldns_key_list *key_list);
```

DESCRIPTION

ldns_key_list_push_key() pushes a key to a keylist

key_list: the key_list to push to

key: the key to push

Returns false on error, otherwise true

ldns_key_list_pop_key() pops the last rr from a keylist

key_list: the rr_list to pop from

Returns NULL if nothing to pop. Otherwise the popped RR

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to dns-team@nlnetlabs.nl or on GitHub at <https://github.com/NLnetLabs/ldns/issues>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_key. And **perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.