

NAME

ldns_rdf_address_reverse - reverse an address rdf

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
ldns_rdf* ldns_rdf_address_reverse(const ldns_rdf *rd);
```

DESCRIPTION

ldns_rdf_address_reverse() reverses an rdf, only actually useful for AAAA and A records. The returned rdf has the type LDNS_RDF_TYPE_DNAME!

***rd:** rdf to be reversed

Returns the reversed rdf (a newly created rdf)

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to dns-team@nlnetlabs.nl or on GitHub at <https://github.com/NLnetLabs/ldns/issues>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_rdf. And **perldoc Net::DNS**, **RFC1034**, **RFC1035**, **RFC4033**, **RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.