

NAME

ldns_rdf_set_size, ldns_rdf_set_type, ldns_rdf_set_data - set rdf attributes

SYNOPSIS

```
#include <stdint.h>
#include <stdbool.h>

#include <ldns/ldns.h>

void ldns_rdf_set_size(ldns_rdf *rd, size_t size);

void ldns_rdf_set_type(ldns_rdf *rd, ldns_rdf_type type);

void ldns_rdf_set_data(ldns_rdf *rd, void *data);
```

DESCRIPTION

ldns_rdf_set_size() sets the size of the rdf.

***rd**: the rdf to operate on

size: the new size

Returns void

ldns_rdf_set_type() sets the size of the rdf.

***rd**: the rdf to operate on

type: the new type

Returns void

ldns_rdf_set_data() sets the size of the rdf.

***rd**: the rdf to operate on

***data**: pointer to the new data

Returns void

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_rdf. And **perldoc Net::DNS**, **RFC1034**, **RFC1035**, **RFC4033**, **RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.