

NAME

ldns_rr_list_cat, ldns_rr_list_push_rr, ldns_rr_list_pop_rr - ldns_rr_list manipulation

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
bool ldns_rr_list_cat(ldns_rr_list *left, const ldns_rr_list *right);
```

```
bool ldns_rr_list_push_rr(ldns_rr_list *rr_list, const ldns_rr *rr);
```

```
ldns_rr* ldns_rr_list_pop_rr(ldns_rr_list *rr_list);
```

DESCRIPTION

ldns_rr_list_cat() concatenates two ldns_rr_lists together. This modifies *left (to extend it and add the pointers from *right).

left: the leftside

right: the rightside

Returns a left with right concatenated to it

ldns_rr_list_push_rr() pushes an rr to an rrlist.

rr_list: the rr_list to push to

rr: the rr to push

Returns false on error, otherwise true

ldns_rr_list_pop_rr() pops the last rr from an rrlist.

rr_list: the rr_list to pop from

Returns NULL if nothing to pop. Otherwise the popped RR

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_rr, *ldns_rr_list*. And **perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.