

NAME

ldns_rr_list_new, ldns_rr_list_free - ldns_rr_list creation and destruction

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
ldns_rr_list* ldns_rr_list_new(void);
```

```
void ldns_rr_list_free(ldns_rr_list *rr_list);
```

DESCRIPTION

ldns_rr_list_new() creates a new rr_list structure.

Returns a new rr_list structure

ldns_rr_list_free() frees an rr_list structure.

rr_list: the list to free

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_rr, *ldns_rr_list*. And **perldoc Net::DNS**, **RFC1034**, **RFC1035**, **RFC4033**, **RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.