

**NAME**

ldns\_rr\_list\_sort - sort a ldns\_rr\_list

**SYNOPSIS**

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
void ldns_rr_list_sort(ldns_rr_list *unsorted);
```

**DESCRIPTION**

*ldns\_rr\_list\_sort()* sorts an rr\_list (canonical wire format). the sorting is done inband.

**unsorted:** the rr\_list to be sorted

Returns void

**AUTHOR**

The ldns team at NLnet Labs.

**REPORTING BUGS**

Please report bugs to [dns-team@nlnetlabs.nl](mailto:dns-team@nlnetlabs.nl) or on GitHub at <https://github.com/NLnetLabs/ldns/issues>

**COPYRIGHT**

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

**SEE ALSO**

*ldns\_rr*, *ldns\_rr\_list*. And **perldoc Net::DNS**, **RFC1034**, **RFC1035**, **RFC4033**, **RFC4034** and **RFC4035**.

**REMARKS**

This manpage was automatically generated from the ldns source code.