

NAME

ldns_rr_mx_preference, ldns_rr_mx_exchange - get MX RR rdata fields

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
ldns_rdf* ldns_rr_mx_preference(const ldns_rr *r);
```

```
ldns_rdf* ldns_rr_mx_exchange(const ldns_rr *r);
```

DESCRIPTION

ldns_rr_mx_preference() returns the mx pref. of a LDNS_RR_TYPE_MX rr

r: the resource record

Returns a ldns_rdf* with the preference or NULL on failure

ldns_rr_mx_exchange() returns the mx host of a LDNS_RR_TYPE_MX rr

r: the resource record

Returns a ldns_rdf* with the name of the MX host or NULL on failure

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at

<http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034 and RFC4035.

REMARKS

This manpage was automatically generated from the ldns source code.