

NAME

ldns_sign_public_dsa, ldns_sign_public_rsamd5, ldns_sign_public_rsasha1 - sign buffer

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
ldns_rdf* ldns_sign_public_dsa(ldns_buffer *to_sign, DSA *key);
```

```
ldns_rdf* ldns_sign_public_rsamd5(ldns_buffer *to_sign, RSA *key);
```

```
ldns_rdf* ldns_sign_public_rsasha1(ldns_buffer *to_sign, RSA *key);
```

DESCRIPTION

ldns_sign_public_dsa() Sign a buffer with the DSA key (hash with SHA1)

to_sign: The ldns_buffer containing raw data that is to be signed

key: The DSA key structure to sign with

Returns a ldns_rdf for the RRSIG ldns_rr

ldns_sign_public_rsamd5() Sign a buffer with the RSA key (hash with MD5)

to_sign: buffer with the data

key: the key to use

Returns a ldns_rdf with the signed data

ldns_sign_public_rsasha1() Sign a buffer with the RSA key (hash with SHA1)

to_sign: buffer with the data

key: the key to use

Returns a ldns_rdf with the signed data

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_sign_public. And **perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.