

**NAME**

ldns\_zone\_push\_rr, ldns\_zone\_push\_rr\_list - add rr's to a ldns\_zone

**SYNOPSIS**

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
bool ldns_zone_push_rr(ldns_zone *z, ldns_rr *rr);
```

```
bool ldns_zone_push_rr_list(ldns_zone *z, const ldns_rr_list *list);
```

**DESCRIPTION**

*ldns\_zone\_push\_rr()* push an single rr to a zone structure. This function use pointer copying, so the rr\_list structure inside z is modified!

**z:** the zone to add to

**rr:** the rr to add

Returns a true on success otherwise false

*ldns\_zone\_push\_rr\_list()* push an rrlist to a zone structure. This function use pointer copying, so the rr\_list structure inside z is modified!

**z:** the zone to add to

**list:** the list to add

Returns a true on success otherwise false

**AUTHOR**

The ldns team at NLnet Labs.

**REPORTING BUGS**

Please report bugs to [ldns-team@nlnetlabs.nl](mailto:ldns-team@nlnetlabs.nl) or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

**COPYRIGHT**

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or

FITNESS FOR A PARTICULAR PURPOSE.

**SEE ALSO**

*ldns\_zone*. And **perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034** and **RFC4035**.

**REMARKS**

This manpage was automatically generated from the ldns source code.