

**NAME**

ldns\_zone\_set\_rrs, ldns\_zone\_set\_soa - ldns\_zone set content

**SYNOPSIS**

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
void ldns_zone_set_rrs(ldns_zone *z, ldns_rr_list *rrlist);
```

```
void ldns_zone_set_soa(ldns_zone *z, ldns_rr *soa);
```

**DESCRIPTION**

*ldns\_zone\_set\_rrs()* Set the zone's contents

**z:** the zone to put the new soa in

**rrlist:** the rrlist to use

*ldns\_zone\_set\_soa()* Set the zone's soa record

**z:** the zone to put the new soa in

**soa:** the soa to set

**AUTHOR**

The ldns team at NLnet Labs.

**REPORTING BUGS**

Please report bugs to [ldns-team@nlnetlabs.nl](mailto:ldns-team@nlnetlabs.nl) or in our bugzilla at

<http://www.nlnetlabs.nl/bugs/index.html>

**COPYRIGHT**

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

**SEE ALSO**

*ldns\_zone*, *ldns\_zone\_rrs*, *ldns\_zone\_soa*. And **perldoc Net::DNS**, **RFC1034**, **RFC1035**, **RFC4033**, **RFC4034** and **RFC4035**.

**REMARKS**

This manpage was automatically generated from the ldns source code.