

NAME

ldns_zone_sort, ldns_zone_glue_rr_list - sort a zone and get the glue records

SYNOPSIS

```
#include <stdint.h>
#include <stdbool.h>

#include <ldns/ldns.h>

void ldns_zone_sort(ldns_zone *zone);

ldns_rr_list* ldns_zone_glue_rr_list(const ldns_zone *z);
```

DESCRIPTION

ldns_zone_sort() Sort the rrs in a zone, with the current impl. this is slow
zone: the zone to sort

ldns_zone_glue_rr_list() Retrieve all resource records from the zone that are glue records. The resulting list does are pointer references to the zone's data.

Due to the current zone implementation (as a list of rr's), this function is extremely slow. Another (probably better) way to do this is to use an ldns_dnssec_zone structure and the ldns_dnssec_mark_and_get_glue() function.

z: the zone to look for glue
Returns the rr_list with the glue

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_zone. And **perldoc Net::DNS**, **RFC1034**, **RFC1035**, **RFC4033**, **RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.