

NAME

mailstats - display mail statistics

SYNOPSIS

mailstats [-c] [-o] [-p] [-P] [-C *cfile*] [-f *stfile*]

DESCRIPTION

The **mailstats** utility displays the current mail statistics.

First, the time at which statistics started being kept is displayed, in the format specified by `ctime(3)`. Then, the statistics for each mailer are displayed on a single line, each with the following white space separated fields:

M	The mailer number.
msgsfr	Number of messages from the mailer.
bytes_from	Kbytes from the mailer.
msgsto	Number of messages to the mailer.
bytes_to	Kbytes to the mailer.
msgsrej	Number of messages rejected.
msgsdis	Number of messages discarded.
msgsqr	Number of messages quarantined.
Mailer	The name of the mailer.

After this display, a line totaling the values for all of the mailers is displayed (preceded with a “T”), separated from the previous information by a line containing only equals (“=”) characters. Another line preceded with a “C” lists the number of TCP connections.

The options are as follows:

- C Read the specified file instead of the default **sendmail** configuration file.
- c Try to use submit.cf instead of the default **sendmail** configuration file.
- f Read the specified statistics file instead of the statistics file specified in the **sendmail** configuration file.
- P Output information in program-readable mode without clearing statistics.
- p Output information in program-readable mode and clear statistics.

- o Don't display the name of the mailer in the output.

The **mailstats** utility exits 0 on success, and >0 if an error occurs.

FILES

/etc/mail/sendmail.cf	The default sendmail configuration file.
/etc/mail/statistics	The default sendmail statistics file.

SEE ALSO

[mailq\(1\)](#), [sendmail\(8\)](#)