

NAME

ne_ssl_trust_cert, ne_ssl_trust_default_ca - functions to indicate that certificates are trusted

SYNOPSIS

```
#include <ne_session.h>
```

```
void ne_ssl_trust_cert(ne_session *session, const ne_ssl_certificate *cert);
```

```
void ne_ssl_trust_default_ca(ne_session *session);
```

DESCRIPTION

To indicate that a given certificate is trusted by the user, the certificate object can be passed to **ne_ssl_trust_cert**. The certificate object is duplicated internally and can subsequently be destroyed.

The SSL library in use by neon may include a default set of CA certificates; calling the **ne_ssl_trust_default_ca** function will indicate that these CAs are trusted by the user.

EXAMPLES

Load the CA certificate stored in /path/to/cacert.pem:

```
ne_session *sess = ne_session_create(...);
ne_ssl_certificate *cert = ne_ssl_cert_read("/path/to/cacert.pem");

if (cert) {
    ne_ssl_trust_cert(sess, cert);
    ne_ssl_cert_free(cert);
} else {
    printf("Could not load CA cert: %s\n", ne_get_error(sess));
}
```

SEE ALSO

ne_ssl_cert_read, ne_ssl_cert_import, ne_ssl_cert_free

AUTHOR

Joe Orton <neon@lists.manyfish.co.uk>

Author.

COPYRIGHT