

NAME

paperconf - print paper configuration information

SYNOPSIS

paperconf [[**-p**] *paper* | **-d** | **-a**] [**-z**] [**-n** | **-N**] [**-s** | **-w** | **-h**] [**-c** | **-m** | **-i**]

DESCRIPTION

paperconf prints information about a given paper. The information that can be obtained is the name of the paper, its size and its width or height. When called without arguments, **paperconf** prints the name of the system- or user-specified paper, obtained by looking in order at the **PAPERSIZE** environment variable, at the contents of the file specified by the **PAPERCONF** environment variable, at the contents of **`\${prefix}/etc/papersize** or by using **letter** as a fall-back value if none of the other alternatives are successful. By default, width and height of the paper are printed in PostScript points.

OPTIONS

-p *paper*

Specify the name of the *paper* about which information is asked.

-d Use the default builtin paper name.

-a Consider all known paper names.

-z If the paper name is unknown, print it but issue a message on the standard error and exit with a non-zero code.

-n Print the name of the paper.

-N Print the name of the paper with the first letter capitalized.

-s Print the size (width followed by height) of the paper.

-w Print the width of the paper.

-h Print the height of the paper.

-c Use centimetres as unit for paper size.

-m Use millimetres as unit for paper size.

-i Use inches as unit for paper size.

ENVIRONMENT

PAPERSIZE Paper size to use regardless of what the papersize file contains.

PAPERCONF Full path to a file containing the paper size to use.

FILES

\${prefix}/etc/papersize Contains the name of the system-wide default paper size to be used if the **PAPERSIZE** and **PAPERCONF** variables are not set.

AUTHOR

Yves Arrouye <arrouye@debian.org>

SEE ALSO

papersize(5)