

NAME

PCRE - Perl-compatible regular expressions

SYNOPSIS

```
#include <pcre.h>
```

```
pcre *pcre_compile2(const char *pattern, int options,
    int *errorcodeptr,
    const char **errptr, int *erroffset,
    const unsigned char *tableptr);
```

```
pcre16 *pcre16_compile2(PCRE_SPTR16 pattern, int options,
    int *errorcodeptr,
    const char **errptr, int *erroffset,
    const unsigned char *tableptr);
```

```
pcre32 *pcre32_compile2(PCRE_SPTR32 pattern, int options,
    int *errorcodeptr,
    const char **errptr, int *erroffset,
    const unsigned char *tableptr);
```

DESCRIPTION

This function compiles a regular expression into an internal form. It is the same as `pcre[16|32]_compile()`, except for the addition of the `errorcodeptr` argument. The arguments are:

pattern A zero-terminated string containing the regular expression to be compiled
options Zero or more option bits
errorcodeptr Where to put an error code
errptr Where to put an error message
erroffset Offset in pattern where error was found
tableptr Pointer to character tables, or NULL to use the built-in default

The option bits are:

| | |
|-------------------|-------------------------------------|
| PCRE_ANCHORED | Force pattern anchoring |
| PCRE_AUTO_CALLOUT | Compile automatic callouts |
| PCRE_BSR_ANYCRLF | \R matches only CR, LF, or CRLF |
| PCRE_BSR_UNICODE | \R matches all Unicode line endings |

PCRE_CASELESS Do caseless matching
 PCRE_DOLLAR_ENDONLY \$ not to match newline at end
 PCRE_DOTALL . matches anything including NL
 PCRE_DUPNAMES Allow duplicate names for subpatterns
 PCRE_EXTENDED Ignore white space and # comments
 PCRE_EXTRA PCRE extra features
 (not much use currently)
 PCRE_FIRSTLINE Force matching to be before newline
 PCRE_JAVASCRIPT_COMPAT JavaScript compatibility
 PCRE_MULTILINE ^ and \$ match newlines within data
 PCRE_NEVER_UTF Lock out UTF, e.g. via (*UTF)
 PCRE_NEWLINE_ANY Recognize any Unicode newline sequence
 PCRE_NEWLINE_ANYCRLF Recognize CR, LF, and CRLF as newline
 sequences
 PCRE_NEWLINE_CR Set CR as the newline sequence
 PCRE_NEWLINE_CRLF Set CRLF as the newline sequence
 PCRE_NEWLINE_LF Set LF as the newline sequence
 PCRE_NO_AUTO_CAPTURE Disable numbered capturing paren-
 theses (named ones available)
 PCRE_NO_AUTO_POSSESS Disable auto-possessification
 PCRE_NO_START_OPTIMIZE Disable match-time start optimizations
 PCRE_NO_UTF16_CHECK Do not check the pattern for UTF-16
 validity (only relevant if
 PCRE_UTF16 is set)
 PCRE_NO_UTF32_CHECK Do not check the pattern for UTF-32
 validity (only relevant if
 PCRE_UTF32 is set)
 PCRE_NO_UTF8_CHECK Do not check the pattern for UTF-8
 validity (only relevant if
 PCRE_UTF8 is set)
 PCRE_UCP Use Unicode properties for \d, \w, etc.
 PCRE_UNGREEDY Invert greediness of quantifiers
 PCRE_UTF16 Run **pcre16_compile()** in UTF-16 mode
 PCRE_UTF32 Run **pcre32_compile()** in UTF-32 mode
 PCRE_UTF8 Run **pcre_compile()** in UTF-8 mode

PCRE must be built with UTF support in order to use PCRE_UTF8/16/32 and PCRE_NO_UTF8/16/32_CHECK, and with UCP support if PCRE_UCP is used.

The yield of the function is a pointer to a private data structure that contains the compiled pattern, or

NULL if an error was detected. Note that compiling regular expressions with one version of PCRE for use with a different version is not guaranteed to work and may cause crashes.

There is a complete description of the PCRE native API in the **pcreapi** page and a description of the POSIX API in the **pcreposix** page.