

NAME**pkg alias** - display configured aliases**SYNOPSIS****pkg alias [-q] [-l] [alias]****pkg alias [--quiet] [--list] [alias]****DESCRIPTION**

pkg alias displays configured aliases. If given the name of an existing alias only shows the aliased arguments to **pkg(8)**. Without arguments all aliases and their respective **pkg(8)** arguments are printed.

OPTIONSThe following options are supported by **pkg alias**:**-l, --list**Print all aliases, one alias per line, without their **pkg(8)** arguments.**-q, --quiet**

Force quiet output (suppress column headers).

FILES**pkg.conf(5)****EXAMPLES**

Display all aliases:

% **pkg alias**Display **pkg(8)** for alias "size":% **pkg alias size****SEE ALSO**

pkg_create(3), **pkg_printf(3)**, **pkg_repos(3)**, **pkg-keywords(5)**, **pkg-lua-script(5)**, **pkg-repository(5)**, **pkg-script(5)**, **pkg-triggers(5)**, **pkg.conf(5)**, **pkg(8)**, **pkg-add(8)**, **pkg-annotate(8)**, **pkg-audit(8)**, **pkg-autoremove(8)**, **pkg-check(8)**, **pkg-clean(8)**, **pkg-config(8)**, **pkg-create(8)**, **pkg-delete(8)**, **pkg-fetch(8)**, **pkg-info(8)**, **pkg-install(8)**, **pkg-lock(8)**, **pkg-query(8)**, **pkg-register(8)**, **pkg-repo(8)**, **pkg-rquery(8)**, **pkg-search(8)**, **pkg-set(8)**, **pkg-shell(8)**, **pkg-shlib(8)**, **pkg-ssh(8)**, **pkg-stats(8)**, **pkg-triggers(8)**, **pkg-update(8)**, **pkg-updating(8)**, **pkg-upgrade(8)**, **pkg-version(8)**, **pkg-which(8)**