

NAME**pkg autoremove** - removes orphan packages**SYNOPSIS****pkg autoremove [-Dnqy]****pkg autoremove [--{dry-run,no-scripts,quiet,yes}]****DESCRIPTION**

pkg autoremove is used for removing orphan packages, which were installed during dependency resolution and are no longer needed.

OPTIONS

The following options are supported by **pkg autoremove**:

-n, --dry-run

Dry-run mode. The list of changes to packages is always printed, but no changes are actually made.

-D, --no-scripts

If a deinstallation script exists for a given package, do not execute it.

-q, --quiet

Force quiet output.

-y, --yes

Assume yes when asked for confirmation before package autoremoval.

ENVIRONMENT

The following environment variables affect the execution of **pkg autoremove**. See **pkg.conf(5)** for further description.

DEFAULT_ALWAYS_YES**ASSUME_ALWAYS_YES****HANDLE_RC_SCRIPTS****PKG_DBDIR**

FILES

See `pkg.conf(5)`.

SEE ALSO

`pkg_create(3)`, `pkg_printf(3)`, `pkg_repos(3)`, `pkg-keywords(5)`, `pkg-lua-script(5)`, `pkg-repository(5)`,
`pkg-script(5)`, `pkg-triggers(5)`, `pkg.conf(5)`, `pkg(8)`, `pkg-add(8)`, `pkg-alias(8)`, `pkg-annotate(8)`,
`pkg-audit(8)`, `pkg-check(8)`, `pkg-clean(8)`, `pkg-config(8)`, `pkg-create(8)`, `pkg-delete(8)`, `pkg-fetch(8)`,
`pkg-info(8)`, `pkg-install(8)`, `pkg-lock(8)`, `pkg-query(8)`, `pkg-register(8)`, `pkg-repo(8)`, `pkg-rquery(8)`,
`pkg-search(8)`, `pkg-set(8)`, `pkg-shell(8)`, `pkg-shlib(8)`, `pkg-ssh(8)`, `pkg-stats(8)`, `pkg-triggers(8)`,
`pkg-update(8)`, `pkg-updating(8)`, `pkg-upgrade(8)`, `pkg-version(8)`, `pkg-which(8)`