

**NAME**

**pkg config** - retrieve the value of a given configuration option

**SYNOPSIS**

**pkg config** *name*

**DESCRIPTION**

**pkg config** retrieve the value of a given configuration option. For lists, one line per entry will be printed, key/values will be printed as one line per key/value pair.

**FILES**

See *pkg.conf(5)*.

**EXAMPLES**

Getting the ABI:

```
% pkg config abi
```

Getting the directories where the repositories configuration are read:

```
% pkg config repos_dir
```

**SEE ALSO**

*pkg\_create(3)*, *pkg\_printf(3)*, *pkg\_repos(3)*, *pkg-keywords(5)*, *pkg-lua-script(5)*, *pkg-repository(5)*,  
*pkg-script(5)*, *pkg-triggers(5)*, *pkg.conf(5)*, *pkg(8)*, *pkg-add(8)*, *pkg-alias(8)*, *pkg-annotate(8)*,  
*pkg-audit(8)*, *pkg-autoremove(8)*, *pkg-check(8)*, *pkg-clean(8)*, *pkg-create(8)*, *pkg-delete(8)*,  
*pkg-fetch(8)*, *pkg-info(8)*, *pkg-install(8)*, *pkg-lock(8)*, *pkg-query(8)*, *pkg-register(8)*, *pkg-repo(8)*,  
*pkg-rquery(8)*, *pkg-search(8)*, *pkg-set(8)*, *pkg-shell(8)*, *pkg-shlib(8)*, *pkg-ssh(8)*, *pkg-stats(8)*,  
*pkg-triggers(8)*, *pkg-update(8)*, *pkg-updating(8)*, *pkg-upgrade(8)*, *pkg-version(8)*, *pkg-which(8)*