

NAME

pkg shell - interact with the pkg database

SYNOPSIS

pkg shell

DESCRIPTION

pkg shell is used to interact with the local or remote database through a sqlite3 console. Extreme care should be taken when using this command.

Do not rely on this command. The underlying schema is subject to change on any release. Use `pkg-query(8)`, `pkg-rquery(8)`, `pkg-search(8)` and `pkg-set(8)` instead for querying and modifying the database. These commands are expected to have a stable API, unlike the database schema.

ENVIRONMENT

The following environment variables affect the execution of **pkg shell**. See `pkg.conf(5)` for further description.

PKG_DBDIR

FILES

See `pkg.conf(5)`.

SEE ALSO

`pkg_create(3)`, `pkg_printf(3)`, `pkg_repos(3)`, `pkg_keywords(5)`, `pkg_lua_script(5)`, `pkg_repository(5)`, `pkg_script(5)`, `pkg_triggers(5)`, `pkg.conf(5)`, `pkg(8)`, `pkg-add(8)`, `pkg-alias(8)`, `pkg-annotate(8)`, `pkg-audit(8)`, `pkg-autoremove(8)`, `pkg-check(8)`, `pkg-clean(8)`, `pkg-config(8)`, `pkg-create(8)`, `pkg-delete(8)`, `pkg-fetch(8)`, `pkg-info(8)`, `pkg-install(8)`, `pkg-lock(8)`, `pkg-query(8)`, `pkg-register(8)`, `pkg-repo(8)`, `pkg-rquery(8)`, `pkg-search(8)`, `pkg-set(8)`, `pkg-shlib(8)`, `pkg-ssh(8)`, `pkg-stats(8)`, `pkg-triggers(8)`, `pkg-update(8)`, `pkg-updating(8)`, `pkg-upgrade(8)`, `pkg-version(8)`, `pkg-which(8)`