

**NAME**

**pkg triggers** - execute triggers that have been deferred

**SYNOPSIS**

**pkg triggers [-q]**

**pkg triggers [--quiet]**

**DESCRIPTION**

**pkg triggers** execute triggers that have been deferred. Triggers can be deferred when the package has been installed on a non-default *rootdir*, for example. Deferred triggers are stored in */var/db/pkg/triggers*.

**OPTIONS**

The following options are supported by **pkg triggers**:

**-q, --quiet** Force quiet output.

**FILES**

See **pkg.conf(5)**.

**SEE ALSO**

**pkg\_create(3)**, **pkg\_printf(3)**, **pkg\_repos(3)**, **pkg-keywords(5)**, **pkg-lua-script(5)**, **pkg-repository(5)**,  
**pkg-script(5)**, **pkg.conf(5)**, **pkg(8)**, **pkg-add(8)**, **pkg-alias(8)**, **pkg-annotate(8)**, **pkg-audit(8)**,  
**pkg-autoremove(8)**, **pkg-check(8)**, **pkg-clean(8)**, **pkg-config(8)**, **pkg-create(8)**, **pkg-delete(8)**,  
**pkg-fetch(8)**, **pkg-info(8)**, **pkg-install(8)**, **pkg-lock(8)**, **pkg-query(8)**, **pkg-register(8)**, **pkg-repo(8)**,  
**pkg-rquery(8)**, **pkg-search(8)**, **pkg-set(8)**, **pkg-shell(8)**, **pkg-shlib(8)**, **pkg-ssh(8)**, **pkg-stats(8)**,  
**pkg-update(8)**, **pkg-updating(8)**, **pkg-upgrade(8)**, **pkg-version(8)**, **pkg-which(8)**