

NAME

posix_spawnattr_getsigdefault, **posix_spawnattr_setsigdefault** - get and set the spawn-sigdefault attribute of a spawn attributes object

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

```
#include <spawn.h>
```

int

```
posix_spawnattr_getsigdefault(const posix_spawnattr_t *restrict attr, sigset_t *restrict sigdefault);
```

int

```
posix_spawnattr_setsigdefault(posix_spawnattr_t *attr, const sigset_t *restrict sigdefault);
```

DESCRIPTION

The **posix_spawnattr_getsigdefault()** function obtains the value of the spawn-sigdefault attribute from the attributes object referenced by *attr*.

The **posix_spawnattr_setsigdefault()** function sets the spawn-sigdefault attribute in an initialized attributes object referenced by *attr*.

The spawn-sigdefault attribute represents the set of signals to be forced to default signal handling in the new process image (if POSIX_SPAWN_SETSIGDEF is set in the spawn-flags attribute) by a spawn operation. The default value of this attribute is an empty signal set.

RETURN VALUES

The **posix_spawnattr_getsigdefault()** and **posix_spawnattr_setsigdefault()** functions return zero.

SEE ALSO

posix_spawn(3), posix_spawnattr_destroy(3), posix_spawnattr_getsigmask(3), posix_spawnattr_init(3), posix_spawnattr_setsigmask(3), posix_spawn(3)

STANDARDS

The **posix_spawnattr_getsigdefault()** and **posix_spawnattr_setsigdefault()** functions conform to IEEE Std 1003.1-2001 ("POSIX.1").

HISTORY

The **posix_spawnattr_getsigdefault()** and **posix_spawnattr_setsigdefault()** functions first appeared in

FreeBSD 8.0.

AUTHORS

Ed Schouten <*ed@FreeBSD.org*>