

**NAME**

**poudriere-logclean** - cleanup old logfiles

**SYNOPSIS**

**poudriere** [*poudriere-options*] **logclean** *subcommand* [*options*]

**DESCRIPTION**

This command will cleanup old logfiles.

One *subcommand* must be supplied.

**SUBCOMMANDS**

- a** Remove all logfiles matching the filter.
- days* How many days old of logfiles to keep matching the filter.
- N count** How many logfiles to keep matching the filter per jail/tree/set combination.

**OPTIONS**

- j name** Specifies the *name* of the jail to filter by.
- n** Dry run, do not actually delete anything.
- B name** Specifies which buildname to match on. May be a glob.
- p tree** Specifies which ports *tree* to use. This can be specified multiple times to consider multiple trees.
- y** Assume yes, do not confirm and just delete the files.
- v** This will show more information during the build. Specify twice to enable debug output.
- z set** This specifies which SET to filter builds by. Use **0** to match on empty SET.

**SEE ALSO**

poudriere(8), poudriere-bulk(8), poudriere-distclean(8), poudriere-image(8), poudriere-jail(8), poudriere-options(8), poudriere-pkgclean(8), poudriere-ports(8), poudriere-queue(8), poudriere-status(8), poudriere-testport(8), poudriere-version(8)

**AUTHORS**

Baptiste Daroussin <bapt@FreeBSD.org>

Bryan Drewery <bdrewery@FreeBSD.org>