

NAME

poudriere-options - configure the options for a given port

SYNOPSIS

```
poudriere [poudriere-options] options [options] -f file
poudriere [poudriere-options] options [options] origin [origin2 [...]]
```

DESCRIPTION

This command configures the options for a given port.

Either a file containing a list of port origins must be supplied with the **-f file** option or a list of port origins must be supplied on the command line.

OPTIONS

This command accepts the following options:

-a architecture

Specifies which *architecture* of FreeBSD to use to show options. (Default: the one of jail *jailname*)

-c Use 'config' target, which will always show the dialog for the given ports.

-C Use 'config-conditional' target, which will only bring up the dialog on new options for the given ports. (This is the default)

-f file Absolute path to a file which contains the list of ports to configure. Ports must be specified in the form *category/port* and shell-style comments are allowed.

-j jailname

If given, configure the options only for the given jail.

-p portstree

Run the configuration inside the given ports tree (by default uses default)

-n Do not be recursive

-r Remove port options instead of configuring them

-s Show port options instead of configuring them

- z set** This specifies which SET to use for the build. See *CUSTOMIZATION* in poudriere(8) for examples of how this is used.

SEE ALSO

poudriere(8), poudriere-bulk(8), poudriere-distclean(8), poudriere-image(8), poudriere-jail(8),
poudriere-logclean(8), poudriere-pkgclean(8), poudriere-ports(8), poudriere-queue(8),
poudriere-status(8), poudriere-testport(8), poudriere-version(8)

AUTHORS

Baptiste Daroussin <bapt@FreeBSD.org>
Bryan Drewery <bdrewery@FreeBSD.org>