

NAME

poudriere pkgclean - cleanup old or unwanted packages

SYNOPSIS

poudriere pkgclean *subcommand* [*options*]
poudriere pkgclean [*options*] *origin* [*origin2* [...]]

DESCRIPTION

This command is used to delete all packages not specified to build. By default packages *not listed* will be deleted; Listed packages, and their dependencies, will be kept.

If **-C** is specified then packages listed on the command line will be deleted rather than kept. Their orphaned dependencies will not be deleted. A second run with a full list of wanted packages is needed to cleanup orphaned dependencies.

Either a subcommand or a list of port origins must be supplied.

SUBCOMMANDS

- A** Remove all packages.
- a** Keep all known ports in the tree.
- f file** Absolute path to a file which contains the list of ports to keep. Ports must be specified in the form *category/port* and shell-style comments are allowed. Multiple **-f file** arguments may be specified at once.

OPTIONS

- C** Delete the listed packages rather than keep them. This can be used to delete specific packages that need to be rebuilt while keeping them in the port list file. **-r** can be specified to delete reverse dependencies as well.
- J number**
This argument specifies how many *number* jobs will run in parallel for gathering package information.
- j name** Jail to use for the packages to inspect.
- N** Do not build package repository when done cleaning.
- n** Dry run, do not actually delete anything.

-O *overlay*

Specify an extra ports tree to use as an overlay. Multiple **-O** *overlay* arguments may be specified to stack them.

These overlays should be setup with `poudriere-ports(8)`.

-p *tree* Specifies which ports *tree* to use. (Default: "default")

-r When **-C** is specified then all reverse dependencies will be deleted as well. This can be used to later force rebuild anything depending on the listed packages.

-R Also clean restricted packages.

-u Force rebuilding and signing the repo, even if no change was made.

-v This will show more information during the build. Specify twice to enable debug output.

-y Assume yes, do not confirm and just delete the files.

-z *set* SET to use for the packages to inspect.

SEE ALSO

`poudriere(8)`, `poudriere-bulk(8)`, `poudriere-distclean(8)`, `poudriere-image(8)`, `poudriere-jail(8)`, `poudriere-logclean(8)`, `poudriere-ports(8)`, `poudriere-queue(8)`, `poudriere-status(8)`, `poudriere-testport(8)`, `poudriere-version(8)`

AUTHORS

Baptiste Daroussin <bapt@FreeBSD.org>

Bryan Drewery <bdrewery@FreeBSD.org>