

NAME

ppdpo - ppd message catalog generator (deprecated)

SYNOPSIS

ppdpo [**-D** *name[=value]*] [**-I** *include-directory*] [**-o** *output-file*] *source-file*

DESCRIPTION

ppdpo extracts UI strings from PPDC source files and updates either a GNU gettext or macOS strings format message catalog source file for translation. **This program is deprecated and will be removed in a future release of CUPS.**

OPTIONS

ppdpo supports the following options:

-D *name[=value]*

Sets the named variable for use in the source file. It is equivalent to using the *#define* directive in the source file.

-I *include-directory*

Specifies an alternate include directory. Multiple *-I* options can be supplied to add additional directories.

-o *output-file*

Specifies the output file. The supported extensions are *.po* or *.po.gz* for GNU gettext format message catalogs and *.strings* for macOS strings files.

NOTES

PPD files are deprecated and will no longer be supported in a future feature release of CUPS. Printers that do not support IPP can be supported using applications such as **ippeveprinter**(1).

SEE ALSO

ppdc(1), **ppdhtml**(1), **ppdi**(1), **ppdmerge**(1), **ppdcfile**(5), CUPS Online Help (<http://localhost:631/help>)

COPYRIGHT

Copyright (C) 2020-2024 by OpenPrinting.