

NAME

pwdcache, user_from_uid, group_from_gid - cache password and group entries

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

#include <pwd.h>

*const char **

user_from_uid(*uid_t uid, int nouser*);

int

uid_from_user(*const char *name, uid_t *uid*);

int

pwdcache_userdb(*int (*setpassent)(int), void (*endpwent)(void),
struct passwd * (*getpwnam)(const char *), struct passwd * (*getpwuid)(uid_t)*);

#include <grp.h>

*const char **

group_from_gid(*gid_t gid, int nogroup*);

int

gid_from_group(*const char *name, gid_t *gid*);

int

pwdcache_groupdb(*int (*setgroupent)(int), void (*endgrent)(void),
struct group * (*getgrnam)(const char *), struct group * (*getgrgid)(gid_t)*);

DESCRIPTION

The **user_from_uid**() function returns the user name associated with the argument *uid*. The user name is cached so that multiple calls with the same *uid* do not require additional calls to **getpwuid**(3). If there is no user associated with the *uid*, a pointer is returned to a string representation of the *uid*, unless the argument *nouser* is non-zero, in which case a NULL pointer is returned.

The **group_from_gid**() function returns the group name associated with the argument *gid*. The group name is cached so that multiple calls with the same *gid* do not require additional calls to **getgrgid**(3). If there is no group associated with the *gid*, a pointer is returned to a string representation of the *gid*, unless

the argument *nogroup* is non-zero, in which case a NULL pointer is returned.

The **uid_from_user()** function returns the uid associated with the argument *name*. The uid is cached so that multiple calls with the same *name* do not require additional calls to `getpwnam(3)`. If there is no uid associated with the *name*, the **uid_from_user()** function returns -1; otherwise it stores the uid at the location pointed to by *uid* and returns 0.

The **gid_from_group()** function returns the gid associated with the argument *name*. The gid is cached so that multiple calls with the same *name* do not require additional calls to `getgrnam(3)`. If there is no gid associated with the *name*, the **gid_from_group()** function returns -1; otherwise it stores the gid at the location pointed to by *gid* and returns 0.

The **pwcache_userdb()** function changes the user database access routines which **user_from_uid()** and **uid_from_user()** call to search for users. The caches are flushed and the existing **endpwent()** method is called before switching to the new routines. *getpwnam* and *getpwuid* must be provided, and *setpassent* and *endpwent* may be NULL pointers.

The **pwcache_groupdb()** function changes the group database access routines which **group_from_gid()** and **gid_from_group()** call to search for groups. The caches are flushed and the existing **endgrent()** method is called before switching to the new routines. *getgrnam* and *getgrgid* must be provided, and *setgroupent* and *endgrent* may be NULL pointers.

ERRORS

If insufficient memory is available, **user_from_uid()** and **group_from_gid()** may return NULL pointers. *errno* is set to ENOMEM.

SEE ALSO

`getgrgid(3)`, `getgrnam(3)`, `getpwnam(3)`, `getpwuid(3)`

HISTORY

The **user_from_uid()** and **group_from_gid()** functions first appeared in 4.4BSD.

The **uid_from_user()** and **gid_from_group()** functions first appeared in NetBSD 1.4.

The **pwcache_userdb()** and **pwcache_groupdb()** functions first appeared in NetBSD 1.6 and FreeBSD 10.0.