

NAME

rs256_pk_new, **rs256_pk_free**, **rs256_pk_from_RSA**, **rs256_pk_from_EVP_PKEY**, **rs256_pk_from_ptr**, **rs256_pk_to_EVP_PKEY** - FIDO2 COSE RS256 API

SYNOPSIS

```
#include <openssl/rsa.h>
```

```
#include <fido/rs256.h>
```

```
rs256_pk_t *
```

```
rs256_pk_new(void);
```

```
void
```

```
rs256_pk_free(rs256_pk_t **pkp);
```

```
int
```

```
rs256_pk_from_EVP_PKEY(rs256_pk_t *pk, const EVP_PKEY *pkey);
```

```
int
```

```
rs256_pk_from_RSA(rs256_pk_t *pk, const RSA *rsa);
```

```
int
```

```
rs256_pk_from_ptr(rs256_pk_t *pk, const void *ptr, size_t len);
```

```
EVP_PKEY *
```

```
rs256_pk_to_EVP_PKEY(const rs256_pk_t *pk);
```

DESCRIPTION

RS256 is the name given in the CBOR Object Signing and Encryption (COSE) RFC to PKCS#1.5 2048-bit RSA with SHA-256. The COSE RS256 API of *libfido2* is an auxiliary API with routines to convert between the different RSA public key types used in *libfido2* and *OpenSSL*.

In *libfido2*, RS256 public keys are abstracted by the *rs256_pk_t* type.

The **rs256_pk_new**() function returns a pointer to a newly allocated, empty *rs256_pk_t* type. If memory cannot be allocated, NULL is returned.

The **rs256_pk_free**() function releases the memory backing **pkp*, where **pkp* must have been previously allocated by **rs256_pk_new**(). On return, **pkp* is set to NULL. Either *pkp* or **pkp* may be NULL, in which case **rs256_pk_free**() is a NOP.

The **rs256_pk_from_EVP_PKEY()** function fills *pk* with the contents of *pkey*. No references to *pkey* are kept.

The **rs256_pk_from_RSA()** function fills *pk* with the contents of *rsa*. No references to *rsa* are kept.

The **rs256_pk_from_ptr()** function fills *pk* with the contents of *ptr*, where *ptr* points to *len* bytes. No references to *ptr* are kept.

The **rs256_pk_to_EVP_PKEY()** function converts *pk* to a newly allocated *EVP_PKEY* type with a reference count of 1. No internal references to the returned pointer are kept. If an error occurs, **rs256_pk_to_EVP_PKEY()** returns NULL.

RETURN VALUES

The **rs256_pk_from_EVP_PKEY()**, **rs256_pk_from_RSA()**, and **rs256_pk_from_ptr()** functions return FIDO_OK on success. On error, a different error code defined in `<fido/err.h>` is returned.

SEE ALSO

`eddsa_pk_new(3)`, `es256_pk_new(3)`, `es384_pk_new(3)`, `fido_assert_verify(3)`, `fido_cred_pubkey_ptr(3)`