

NAME

strcasecmp, **strncasecmp** - compare strings, ignoring case

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

```
#include <strings.h>
```

int

```
strcasecmp(const char *s1, const char *s2);
```

int

```
strncasecmp(const char *s1, const char *s2, size_t len);
```

```
#include <strings.h>
```

```
#include <xlocale.h>
```

int

```
strcasecmp_l(const char *s1, const char *s2, locale_t loc);
```

int

```
strncasecmp_l(const char *s1, const char *s2, size_t len, locale_t loc);
```

DESCRIPTION

The **strcasecmp()** and **strncasecmp()** functions compare the null-terminated strings *s1* and *s2*.

The **strncasecmp()** function compares at most *len* characters. The **strcasecmp_l()** and **strncasecmp_l()** functions do the same as their non-locale versions above, but take an explicit locale rather than using the current locale.

RETURN VALUES

The functions **strcasecmp()** and **strncasecmp()** return an integer greater than, equal to, or less than 0, depending on whether *s1* is lexicographically greater than, equal to, or less than *s2* after translation of each corresponding character to lower-case. The strings themselves are not modified. The comparison is done using unsigned characters, so that '\200' is greater than '\0'. The functions **strcasecmp_l()** and **strncasecmp_l()** do the same but take explicit locales.

SEE ALSO

bcmp(3), memcmp(3), strcmp(3), strcoll(3), strxfrm(3), tolower(3), wscasecmp(3)

HISTORY

The **strcasecmp()** and **strncasecmp()** functions first appeared in 4.4BSD. Their prototypes existed previously in *<string.h>* before they were moved to *<strings.h>* for IEEE Std 1003.1-2001 ("POSIX.1") compliance.