

NAME

stringprep_utf8_to_ucs4 - API function

SYNOPSIS

```
#include <stringprep.h>
```

```
uint32_t * stringprep_utf8_to_ucs4(const char * str, ssize_t len, size_t * items_written);
```

ARGUMENTS

const char * str

a UTF-8 encoded string

ssize_t len the maximum length of *str* to use. If *len* < 0, then the string is nul-terminated.

size_t * items_written

location to store the number of characters in the result, or **NULL**.

DESCRIPTION

Convert a string from UTF-8 to a 32-bit fixed width representation as UCS-4. The function now performs error checking to verify that the input is valid UTF-8 (before it was documented to not do error checking).

Return value: a pointer to a newly allocated UCS-4 string. This value must be deallocated by the caller.

REPORTING BUGS

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU Libidn home page: <http://www.gnu.org/software/libidn/>

COPYRIGHT

Copyright (C) 2002-2021 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libidn** is maintained as a Texinfo manual. If the **info** and **libidn** programs are properly installed at your site, the command

info libidn

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/libidn/manual/>