

**NAME**

tld\_default\_table - API function

**SYNOPSIS**

```
#include <tld.h>
```

```
const Tld_table * tld_default_table(const char * tld, const Tld_table ** overrides);
```

**ARGUMENTS**

const char \* tld

TLD name (e.g. "com") as zero terminated ASCII byte string.

const Tld\_table \*\* overrides

Additional zero terminated array of **Tld\_table** info-structures for TLDs, or **NULL** to only use library default tables.

**DESCRIPTION**

Get the TLD table for a named TLD, using the internal defaults, possibly overridden by the (optional) supplied tables.

Return value: Return structure corresponding to TLD *tld\_str*, first looking through *overrides* then thru built-in list, or **NULL** if no such structure found.

**REPORTING BUGS**

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU Libidn home page: <http://www.gnu.org/software/libidn/>

**COPYRIGHT**

Copyright (C) 2002-2021 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **libidn** is maintained as a Texinfo manual. If the **info** and **libidn** programs are properly installed at your site, the command

```
info libidn
```

should give you access to the complete manual. As an alternative you may obtain the manual from:

**<http://www.gnu.org/software/libidn/manual/>**