

NAME

tld_get_4 - API function

SYNOPSIS

```
#include <tld.h>
```

```
int tld_get_4(const uint32_t * in, size_t inlen, char ** out);
```

ARGUMENTS

const uint32_t * in

Array of unicode code points to process. Does not need to be zero terminated.

size_t inlen Number of unicode code points.

char ** out Zero terminated ascii result string pointer.

DESCRIPTION

Isolate the top-level domain of *in* and return it as an ASCII string in *out*.

Return value: Return **TLD_SUCCESS** on success, or the corresponding **Tld_rc** error code otherwise.

REPORTING BUGS

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU Libidn home page: <http://www.gnu.org/software/libidn/>

COPYRIGHT

Copyright (C) 2002-2021 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libidn** is maintained as a Texinfo manual. If the **info** and **libidn** programs are properly installed at your site, the command

```
info libidn
```

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/libidn/manual/>