

NAME

tld_get_table - API function

SYNOPSIS

```
#include <tld.h>
```

```
const Tld_table * tld_get_table(const char * tld, const Tld_table ** tables);
```

ARGUMENTS

const char * tld

TLD name (e.g. "com") as zero terminated ASCII byte string.

const Tld_table ** tables

Zero terminated array of **Tld_table** info-structures for TLDs.

DESCRIPTION

Get the TLD table for a named TLD by searching through the given TLD table array.

Return value: Return structure corresponding to TLD *tld* by going thru *tables* , or return **NULL** if no such structure is found.

DESCRIPTION

Get the TLD table for a named TLD by searching through the given TLD table array.

Return value: Return structure corresponding to TLD *tld* by going thru *tables* , or return **NULL** if no such structure is found.

REPORTING BUGS

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU Libidn home page: <http://www.gnu.org/software/libidn/>

COPYRIGHT

Copyright (C) 2002-2021 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libidn** is maintained as a Texinfo manual. If the **info** and **libidn** programs

are properly installed at your site, the command

info libidn

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/libidn/manual/>