

NAME

tld_get_z - API function

SYNOPSIS

```
#include <tld.h>
```

```
int tld_get_z(const char * in, char ** out);
```

ARGUMENTS

const char * in

Zero terminated character array to process.

char ** out Zero terminated ascii result string pointer.

DESCRIPTION

Isolate the top-level domain of *in* and return it as an ASCII string in *out* . The input string *in* may be UTF-8, ISO-8859-1 or any ASCII compatible character encoding.

Return value: Return **TLD_SUCCESS** on success, or the corresponding **Tld_rc** error code otherwise.

REPORTING BUGS

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU Libidn home page: <http://www.gnu.org/software/libidn/>

COPYRIGHT

Copyright (C) 2002-2021 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libidn** is maintained as a Texinfo manual. If the **info** and **libidn** programs are properly installed at your site, the command

info libidn

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/libidn/manual/>