

**NAME**

xcb\_change\_save\_set - Changes a client's save set

**SYNOPSIS**

```
#include <xcb/xproto.h>
```

**Request function**

```
xcb_void_cookie_t xcb_change_save_set(xcb_connection_t *conn, uint8_t mode,  
xcb_window_t window);
```

**REQUEST ARGUMENTS**

*conn*           The XCB connection to X11.

*mode*           One of the following values:

*XCB\_SET\_MODE\_INSERT*

                  TODO: NOT YET DOCUMENTED.

*XCB\_SET\_MODE\_DELETE*

                  TODO: NOT YET DOCUMENTED.

                  Insert to add the specified window to the save set or Delete to delete it from the save set.

*window*         The window to add or delete to/from your save set.

**DESCRIPTION**

TODO: explain what the save set is for.

This function either adds or removes the specified window to the client's (your application's) save set.

**RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_change\_save\_set\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

*xcb\_match\_error\_t*

You created the specified window. This does not make sense, you can only add

windows created by other clients to your save set.

*xcb\_value\_error\_t*

You specified an invalid mode.

*xcb\_window\_error\_t*

The specified window does not exist.

## **SEE ALSO**

**xcb-requests(3)**, **xcb\_reparent\_window(3)**

## **AUTHOR**

Generated from xproto.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.