

NAME

xcb_clear_area -

SYNOPSIS

```
#include <xcb/xproto.h>
```

Request function

```
xcb_void_cookie_t xcb_clear_area(xcb_connection_t *conn, uint8_t exposures,  
xcb_window_t window, int16_t x, int16_t y, uint16_t width, uint16_t height);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>exposures</i>	TODO: NOT YET DOCUMENTED.
<i>window</i>	TODO: NOT YET DOCUMENTED.
<i>x</i>	TODO: NOT YET DOCUMENTED.
<i>y</i>	TODO: NOT YET DOCUMENTED.
<i>width</i>	TODO: NOT YET DOCUMENTED.
<i>height</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_clear_area_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from xproto.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.