

NAME

xcb_composite_get_overlay_window -

SYNOPSIS

```
#include <xcb/composite.h>
```

Request function

```
xcb_composite_get_overlay_window_cookie_t
    xcb_composite_get_overlay_window(xcb_connection_t *conn, xcb_window_t window);
```

Reply datastructure

```
typedef struct xcb_composite_get_overlay_window_reply_t {
    uint8_t    response_type;
    uint8_t    pad0;
    uint16_t   sequence;
    uint32_t   length;
    xcb_window_t overlay_win;
    uint8_t    pad1[20];
} xcb_composite_get_overlay_window_reply_t;
```

Reply function

```
xcb_composite_get_overlay_window_reply_t
    *xcb_composite_get_overlay_window_reply(xcb_connection_t *conn,
    xcb_composite_get_overlay_window_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

window TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_COMPOSITE_GET_OVERLAY_WINDOW*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

xcb_composite_get_overlay_window(3) XCB Requests xcb_composite_get_overlay_window(3)

overlay_win TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_composite_get_overlay_window_cookie_t*. Errors have to be handled when calling the reply function *xcb_composite_get_overlay_window_reply*.

If you want to handle errors in the event loop instead, use *xcb_composite_get_overlay_window_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from composite.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.